



FEATURES:

- Qualifications: ETL, T24, Energy Star, Damp Location
- Electrical: 120–277V, 50/60 Hz input. Dimmed via 0–10V
- Field-adjustable CCT (2700K–5000K) via dip switches on housing
- Field-adjustable wattage via dip switches on housing
- Construction: 0.5mm metal with white powder coating
- Diffuser: 2.6mm LED frosted PC material
- Surface mounted standard; P59 pendant mount available
- Optional: Integral occupancy sensor (OCC) or emergency battery (EM)

DLA SERIES

DLA

Architectural Linear

Built out of high quality metal. This fixture is not only bright, but durable. Our linear line is an easy choice for all your hallway, back of house, storage, and other locations that need a lot of light with a very easy installation method.

Fixture Type:

Job Information:

LINE DRAWINGS:

Model	L	W	H
DLA2	23.6in	2.36in	3.47in
DLA4	46.1in	2.36in	3.47in
DLA8	92.1in	2.36in	3.47in

DLA SERIES

Ex: **DLA-4-P59-OCC** — Ordering code example

SERIES DLA Series Architectural	LENGTH Fixture Length (feet)	MOUNTING Mounting Option
DLA Architectural Linear	2 23.6" Nominal	— Surface Mount (standard)
	4 46.1" Nominal	
	8 92.2" Nominal	P59 Pendant Mount 59" cables

CONSTRUCTION:

- 0.5mm metal housing with white powder coating
- 2.6mm LED frosted PC diffuser material
- White finish standard; custom finish available

LED & ELECTRICAL:

- Input: 120–277V, 50/60Hz
- Dimming: 0–10V
- Beam angle: 133°
- CRI: 80 standard

FIELD ADJUSTABLE:

- Color temperature (2700K–5000K) selectable via dip switches
- Wattage selectable via dip switches on housing interior

MOUNTING OPTIONS:

- Surface mounted standard (leave blank in order code)
- P59 — includes 60" aircraft cables, 59" power cable, bracket bars, Ø4.33" white canopies, pair of cable grippers

CERTIFICATIONS:

- ETL Listed
- Title 24 (T24) Compliant
- Energy Star Rated
- Damp Location Rated

LUMEN & WATTAGE GUIDE

DLA	WATTAGE	27K	30K	35K	40K	50K
8	55	5635	5750	6037.5	6325	6900
8	65	6762	6900	7245	7590	8280
8	80	9016	9200	9660	10120	11040
4	25	2817.5	2875	3018.75	3162.5	3450
4	30	3381	3450	3622.5	3795	4140
4	40	4508	4600	4830	5060	5520
2	15	1690.5	1725	1811.25	1897.5	2070
2	20	2254	2300	2415	2530	2760
2	25	2817.5	2875	3018.75	3162.5	3450

Full photometric report available at directled.co

MOUNTING OPTIONS

Standard Mounting Option

Mounts to any surface

P59 —

Mounting option includes:

- 60" aircraft cables
- 59" power cable
- Bracket bars
- Ø 4.33" white canopies
- Pair of cable grippers

PERFORMANCE DETAILS

Materials	0.5mm metal with white powder coating; 2.6mm frosted PC diffuser
Dimensions (2FT)	23.6" L × 2.36" W × 3.47" H
Dimensions (4FT)	46.1" L × 2.36" W × 3.47" H
Input Voltage	120–277V, 50/60Hz
CRI	80
Beam Angle	133°
Color Temperature	2700K / 3000K / 3500K / 4000K / 5000K (field selectable)
Dimming	0–10V
Finish	White standard; Custom finish available
Operating Temp	-20°F to 100°F
Mounting	Surface standard; P59 pendant available
Certifications	ETL, T24, Energy Star, Damp Location
Warranty	5 Years

