

## BEFORE YOU BEGIN

### WARNING

Make sure power is **OFF** at the electrical panel before starting installation or any maintenance. Indoor installation only unless otherwise noted.

### SAFETY

This fixture must be wired in accordance with local electrical codes and ordinances. All work should be done by a qualified electrician.

### NOTE

Read all instructions before installing. Keep this sheet for future reference.

### WET

Approved for wet location when sealed per these instructions. Use silicone caulk between gasket and ceiling.

## INSTALLATION

- 01 Turn power OFF at the electrical panel.
- 02 Remove the lens housing — set lens aside.
- 03 Mount the back-plate to the ceiling junction box with the screws provided. (FIG. 1)
- 04 Make electrical connections: black-black (or red for 277 V), white-white, ground-green. (FIG. 2)
- 05 Tuck wires into the back of the housing.
- 06 Seat the housing onto the back-plate and secure with side screws.
- 07 Reinstall the lens and verify a clean gasket seal.
- 08 Run a continuous bead of clear silicone around the ceiling perimeter where the canopy meets the surface.
- 09 Restore power and verify operation.

## WIRING REFERENCE

<input type="checkbox"/> Line — 120 V	BLACK
<input type="checkbox"/> Line — 277 V	RED
<input type="checkbox"/> Neutral	WHITE
<input type="checkbox"/> Ground	GREEN / BARE

### CAP

Always cap the unused line wire (black or red) with a wire nut and tuck securely.

## FIGURES

